

Liaz DS 0102

Wysięg L_v (m)	Długość wysięgnika							
	$L_{11} = 9m$		$L_{12} = 12m$		$L_{13} = 15m$		$L_{14} = 21m$	
	Udźwig Q (t) i wysokość podnoszenia H (m)							
	Q	H	Q	H	Q	H	Q	H
3.00	10.00	9.00	8.10	12.30	6.30	15.50	-	-
4.00	6.50	8.40	5.50	11.90	4.25	15.20	-	-
4.50	-	-	-	-	-	-	1.50	21.30
5.00	4.60	7.50	4.10	11.30	3.25	14.70	1.38	21.10
6.00	3.70	6.40	3.20	10.70	2.60	14.20	1.20	20.80
7.00	2.95	4.60	2.95	9.70	2.10	13.70	1.06	20.40
7.30	2.75	3.80	-	-	-	-	-	-
8.00	-	-	2.05	8.60	1.80	12.90	0.95	19.90
9.00	-	-	1.70	7.30	1.50	12.00	0.84	19.30
10.00	-	-	-	-	1.30	11.00	0.75	18.90
10.10	-	-	1.40	5.00	-	-	-	-
11.00	-	-	-	-	1.10	9.70	0.67	18.00
12.00	-	-	-	-	0.95	8.10	0.61	17.40
13.00	-	-	-	-	0.84	5.70	0.55	16.50
14.00	-	-	-	-	-	-	0.50	15.50
15.00	-	-	-	-	-	-	0.44	14.30
16.00	-	-	-	-	-	-	0.40	13.10
17.00	-	-	-	-	-	-	0.36	11.60
18.00	-	-	-	-	-	-	0.32	9.60
18.60	-	-	-	-	-	-	0.30	7.90
Ilość pasm	6 pasm liny						1 pasmo liny	

